



Kokopelli Sports Racer

- · CSR or DSR depending on engine choice
- CVT Drive
- 3 cylinder two stroke Rotax or Crankshop engines, 150-255 HP
- Fully TIG welded chassis
- Willwood Calipers 10" ø brake discs front and rear
- · Fuel Safe Pro-cells
- Billet uprights, hubs, etc.
- Adjustable anti-rolls bars front and rear
- SPA mirrors
- Pushrod/bellcrank suspension
- · Fluidyne radiators
- Willans 6 point harness
- Alpha steering wheel
- Titan steering rack



Kokopelli DSR Specifications

Weight 780 lbs. (354 kg) with Rotax 780 engine

Overall width 64 inches (1626 mm)
Overall length 141 inches (3581 mm)

154 inches (3912 mm) with wing

Overall height 31.5 inches (800 mm)

Front track 56 inches (1422 mm)

Rear track 53 inches (1346 mm)

Wheel base 88 inches (2235 mm)

Front wheels 13" x 8"

Front wheels 13" x 8"

Rear wheels 13" x 10"

Front tires Hoosier R33 7.5-20-13 (recommended)
Rear tires Hoosier R33 10-21-13 (recommended)

Front brakes 10"Ø with Willwood 2 piston caliper 10"Ø with Willwood 2 piston caliper

Brake pads Willwood Polymatrix "B"

Fuel capacity

1 cell 6.8 gal. (25.7 liters), base DSR 2 cell 14.6 gal. (55.3 liters), 150+ HP

Dampers (F & R) Carrera - alloy body - coil over 300 lb. 2" x 5"

Rear springs 400 lb. 2" x 5"

Rear springs 400 lb. 2" x 5"

500 lb. 2" x 5" with wing



Kokopelli SportsRacer Basic Chassis / Body Kit

The Basic Body / Chassis Kit is offered for those who would like to take advantage of the aerodynamic and aesthetic qualities of the **Kokopelli SportsRacer** but already have a source for chassis components.

The bare spaceframe is supplied without suspension pick-up points so you can customize geometry for your uprights, etc. Standard **Kokopelli** suspension is available in kit form for an additional charge.

Chassis are available in independent rear or live axle, motorcycle or 2 stroke CVT configuration.

•	Chassis	95 lbs.
0	Fiberglass Body	73 lbs.
	Height	31 in.
0	Length	136 in.
0	Width	64 in.
0	Wheelbase Range	85-92 in.